

Signal

Nagman

mA & V Calibrator

**Portable, Handy, Easy to carry
& Sturdy Case with grip**


Basic Accuracy : $\pm 0.05\%$ F.S.

*Capability to Measure & Simulate
Voltage & Current Readings*

Model

NAGMAN 05

- Compact, Light Weight Unit with Holster
- Capability to Measure & Simulate Voltage & Current Readings
- Capability to provide Loop Supply (24V) for Transmitters



(P.T.O)

SPECIFICATIONS

MEASURING FUNCTIONS

Input	Range / Type	Input Range	Resolution	Accuracy	Remarks
Voltage	28 V	-0.2 to 28 V	1 mV	$\pm 0.02\%$ reading ± 2 mV	Impedance 2 M Ω
Current	20 mA	-1 to 22 mA	0.001 mA	$\pm 0.02\%$ reading ± 4 μ A	Impedance 20 M Ω
Loop Current	20 mA	0 to 22 mA	0.001 mA	$\pm 0.02\%$ reading ± 4 μ A	Supply 24 V Loop Power

OUTPUT FUNCTIONS

Output	Range / Type	Output Range	Resolution	Accuracy	Remarks
Current	20 mA	0 to 22 mA	0.001 mA	$\pm 0.05\%$ set value ± 4 μ A	20 mA, maximum overload is 1 k Ω
Analog Transducer	-20 mA	0 to 22 mA	0.001 mA	$\pm 0.05\%$ set value ± 4 μ A	20 mA, maximum overload is 1 k Ω
Loop Power	24 V	---	---	$\pm 10\%$	Maximum output current 25 mA

STANDARD DELIVERY

- mA & V Calibrator – Model : Nagman 05
- 9V Alkaline Battery
- Operation Manual
- Test Leads
- Traceable Calibration Certificate

OPTIONALS

- Calibration Certificate from NABL Accredited – as per ISO/IEC 17025:2005 Laboratory

Product of

Nagman Instruments & Electronics (P) Ltd.

- Comprehensive Calibration Solutions (Standards / Systems / Packages / Software / Services)
Chennai – 600 123. INDIA.



Domestic Sales
International Sales

044 – 2252 2800, 2252 3240
+91-44-26811704, 26811708

Fax 044 – 2252 3240
Fax +91-44-26811703

E-Mail mktgchennai@nagman.com
E-Mail exports@nagman.com

www.nagman.com

